


Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr

Mündungsabschluss (ohne Dämmwolle)


Art.-Nr. 3510-



D	Da	A	B	S
113	176	195	125	70
130	193	195	125	70
150	213	195	125	70
160	223	195	125	70
180	243	230	130	100
200	263	230	130	100
250	313	230	130	100
300	363	230	130	100
350	413	230	130	100
400	463	230	130	100
450	513	230	130	100
500	563	230	130	100
600	663	230	130	100

Dachdurchführung mit Niroblech, Flachdach


Art.-Nr. 3514-



D	Da	A
113	206	280
130	223	280
150	243	280
160	253	280
180	273	280
200	293	280
250	343	280
300	393	280
350	443	280
400	493	280
450	543	280
500	593	280
600	693	280

Regenhaube


Art.-Nr. 3547-



D	Da	S
113	176	70
130	193	70
150	213	70
160	223	70
180	243	100
200	263	100
250	313	100
300	363	100
350	413	100
400	463	100
450	513	100
500	563	100
600	663	100

Dachdurchführung mit Bleischürze, 0° - 15°


Art.-Nr. 3548-



D	Da	A
113	206	160
130	223	160
150	243	160
160	253	160
180	273	160
200	293	160
250	343	160
300	393	160
350	443	160
400	493	160
450	543	160
500	593	160
600	693	160

Regenhaube mit Funkenschutz


Art.-Nr. 3547- F



D	Da	S
113	176	70
130	193	70
150	213	70
160	223	70
180	243	100
200	263	100
250	313	100
300	363	100
350	413	100
400	463	100
450	513	100
500	563	100
600	663	100

Dachdurchführung mit Bleischürze, 15° - 30°


Art.-Nr. 3515-



D	Da	A
113	206	160
130	223	160
150	243	160
160	253	160
180	273	160
200	293	160
250	343	160
300	393	160
350	443	160
400	493	160
450	543	160
500	593	160
600	693	160

Regenhaube mit Windabweiser


Art.-Nr. 3511-



D	Da	S
113	176	70
130	193	70
150	213	70
160	223	70
180	243	100
200	263	100
250	313	100
300	363	100
350	413	100
400	463	100
450	513	100
500	563	100
600	663	100

Dachdurchführung mit Bleischürze, 25° - 35°

Art.-Nr. 3516-



D	Da	A
113	206	160
130	223	160
150	243	160
160	253	160
180	273	160
200	293	160
250	343	160
300	393	160
350	443	160
400	493	160
450	543	160
500	593	160
600	693	160


Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr


Dachdurchführung mit Bleischürze, 30° - 45°

Art.-Nr. 3509-	D	Da	A
	113	206	160
	130	223	160
	150	243	160
	160	253	160
	180	273	160
	200	293	160
	250	343	160
	300	393	160
	350	443	160
	400	493	160
	450	543	160
	500	593	160
	600	693	160




Blende mit Hinterlüftung 90°, oder Winkelangabe

Art.-Nr. 3523-	H	D	Da	Blechgröße
		113	176	
		130	193	
		150	213	
		160	223	
		180	243	
		200	263	
		250	313	umlaufend 130 mm und umlaufend 250 mm
		300	363	
		350	413	
		400	463	
		450	513	
		500	563	
		600	663	




Firstabdeckung

Art.-Nr. 3549-	D	Da	A
	113	206	160
	130	223	160
	150	243	160
	160	253	160
	180	273	160
	200	293	160
	250	343	160
	300	393	160
	350	443	160
	400	493	160
	450	543	160
	500	593	160
	600	693	160




Zwischenstütze

Art.-Nr. 3557-	D	Da	A	B	C	S
	113	176	250	180	290	70
	130	193	250	180	290	70
	150	213	250	180	290	70
	160	223	250	180	320	70
	180	243	333	233	320	100
	200	263	333	233	360	100
	250	313	333	233	410	100
	300	363	333	233	460	100
	350	413	333	233	510	100
	400	463	333	233	560	100
	450	513	333	233	610	100
	500	563	333	233	660	100
	600	663	333	233	760	100




Blende 2-teilig 90°, eckig

Art.-Nr. 3523-	D	Da	Blechgröße
	113	176	
	130	193	
	150	213	
	160	223	
	180	243	umlaufend 100 mm und umlaufend 220 mm
	200	263	
	250	313	
	300	363	
	350	413	
	400	463	
	450	513	
	500	563	
	600	663	




Abdeckblech Dw/Ew runder Einschub

Art.-Nr. 3560-	D	Da	A	B	C	S
	113	176	250	90	300	150
	130	193	250	90	300	150
	150	213	250	90	300	150
	160	223	250	90	300	150
	180	243	333	125	300	198
	200	263	333	125	400	198
	250	313	333	125	450	198
	300	363	333	125	500	198
	350	413	333	125	550	198
	400	463	333	125	600	198
	450	513	333	125	650	198
	500	563	333	125	700	198
	600	663	333	125	800	198




Blende 2-teilig eckig, mit Winkelangabe

Art.-Nr. 3523- W	D	Da	Blechgröße
	113	176	
	130	193	
	150	213	
	160	223	
	180	243	umlaufend 100 mm und umlaufend 220 mm
	200	263	
	250	313	
	300	363	
	350	413	
	400	463	
	450	513	
	500	563	
	600	663	



Abdeckblech Dw/Ew eckig u. Plewa Einschub

Art.-Nr. 3560- E	D	Da	A	S	B	C
	113	176	245	200		
	130	193	245	200		
	150	213	245	200	Nach Angabe	
	160	223	245	200	Z.B.	
	180	243	245	200	180x180 oder 180x200	Nach Angabe
	200	263	245	200		
	250	313	245	200		
	300	363	245	200	Plewa hat	
	350	413	245	200	Abgerundete Ecken	
	400	463	245	200		
	450	513	245	200		
	500	563	245	200		
	600	663	245	200		



Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr

Abspannschelle für Seil / Teleskopstange


Art.-Nr. 3521-



D	Da
113	176
130	193
150	213
160	223
180	243
200	263
250	313
300	363
350	413
400	463
450	513
500	563
600	663

Regenkragen konisch


Art.-Nr. 3517-



D	Da	C
113	176	286
130	193	303
150	213	323
160	223	333
180	243	353
200	263	373
250	313	423
300	363	473
350	413	523
400	463	573
450	513	623
500	563	673
600	663	773

Sparrenbefestigung einfach


Art.-Nr. 3520-



D	Da	C
113	176	2096
130	193	2113
150	213	2133
160	223	2143
180	243	2163
200	263	2183
250	313	2233
300	363	2283
350	413	2333
400	463	2383
450	513	2433
500	563	2483
600	663	2583

Sparrenbefestigung verstärkt


Art.-Nr. 3520- V



D	Da	C
113	176	1000
130	193	1000
150	213	1000
160	223	1000
180	243	1000
200	263	1000
250	313	1000
300	363	1000
350	413	1000
400	463	1000
450	513	1000
500	563	1000
600	663	1000

Längenelement 1000 mm


Art.-Nr. 3527-



D	Da	A	B	S
113	176	1000	930	70
130	193	1000	930	70
150	213	1000	930	70
160	223	1000	930	70
180	243	1000	900	100
200	263	1000	900	100
250	313	1000	900	100
300	363	1000	900	100
350	413	1000	900	100
400	463	1000	900	100
450	513	1000	900	100
500	563	1000	900	100
600	663	1000	900	100

Längenelement 1000 mm kürzbar

Art.-Nr. 3527- K




D	Da	A	B	S
113	176	1000	930	70
130	193	1000	930	70
150	213	1000	930	70
160	223	1000	930	70
180	243	1000	900	100
200	263	1000	900	100
250	313	1000	900	100
300	363	1000	900	100
350	413	1000	900	100
400	463	1000	900	100
450	513	1000	900	100
500	563	1000	900	100
600	663	1000	900	100

enge
Seiten
ohne
Sicken

Längenelement 500 mm


Art.-Nr. 3528-



D	Da	A	B	S
113	176	500	430	70
130	193	500	430	70
150	213	500	430	70
160	223	500	430	70
180	243	500	400	100
200	263	500	400	100
250	313	500	400	100
300	363	500	400	100
350	413	500	400	100
400	463	500	400	100
450	513	500	400	100
500	563	500	400	100
600	663	500	400	100

Längenelement 333 mm

Art.-Nr. 3529-



D	Da	A	B	S
113	176	333	263	70
130	193	333	263	70
150	213	333	263	70
160	223	333	263	70
180	243	333	233	100
200	263	333	233	100
250	313	333	233	100
300	363	333	233	100
350	413	333	233	100
400	463	333	233	100
450	513	333	233	100
500	563	333	233	100
600	663	333	233	100


Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr

Längenelement 250 mm

Art.-Nr. 3530-



D	Da	A	B	S
113	176	250	180	70
130	193	250	180	70
150	213	250	180	70
160	223	250	180	70
180	243	250	150	100
200	263	250	150	100
250	313	250	150	100
300	363	250	150	100
350	413	250	150	100
400	463	250	150	100
450	513	250	150	100
500	563	250	150	100
600	663	250	150	100

Rosette

Art.-Nr. 3522-



D	Da
113	176
130	193
150	213
160	223
180	243
200	263
250	313
300	363
350	413
400	463
450	513
500	563
600	663

Umlaufend um Da ca. 80 mm

Klemmband statisch


Art.-Nr. 3531- st



D	Da
113	176
130	193
150	213
160	223
180	243
200	263
250	313
300	363
350	413
400	463
450	513
500	563
600	663

Winkel 15°


Art.-Nr. 3532-



D	Da	A	B	S
113	176	125	55	70
130	193	125	55	70
150	213	125	55	70
160	223	125	55	70
180	243	167	67	100
200	263	167	67	100
250	313	167	67	100
300	363	167	67	100
350	413	200	100	100
400	463	200	100	100
450	513	200	100	100
500	563	200	100	100
600	663	200	100	100

Feuerungsanschluss 90°


Art.-Nr. 3536-



D	Da	A	B	C	H	S
113	176	400	330	105	140	70
130	193	400	330	115	140	70
150	213	400	330	125	140	70
160	223	400	330	140	130	70
180	243	490	390	145	145	100
200	263	510	410	155	155	100
250	313	560	460	180	180	100
300	363	610	510	205	205	100
350	413	660	560	230	230	100
400	463	710	610	255	255	100
450	513	780	680	290	290	100
500	563	810	710	305	305	100
600	663	910	810	355	355	100

Winkel 30°


Art.-Nr. 3533-



D	Da	A	B	S
113	176	125	55	70
130	193	125	55	70
150	213	125	55	70
160	223	125	55	70
180	243	167	67	100
200	263	167	67	100
250	313	167	67	100
300	363	200	100	100
350	413	200	100	100
400	463	200	100	100
450	513	200	100	100
500	563	225	125	100
600	663	225	125	100

Feuerungsanschluss 45°


Art.-Nr. 3537-



D	Da	A	B	C	H	S
113	176	420	350	225	225	70
130	193	450	380	250	250	70
150	213	480	410	275	275	70
160	223	500	430	291	291	70
180	243	590	490	315	315	100
200	263	620	520	340	340	100
250	313	690	590	400	400	100
300	363	760	660	460	460	100
350	413	830	730	520	520	100
400	463	900	800	580	580	100
450	513	970	870	640	640	100
500	563	1045	945	700	700	100
600	663	1185	1085	825	825	100

Winkel 45°

Art.-Nr. 3534-



D	Da	A	B	S
113	176	140	70	70
130	193	140	70	70
150	213	140	70	70
160	223	140	70	70
180	243	200	100	100
200	263	200	100	100
250	313	200	100	100
300	363	250	150	100
350	413	250	150	100
400	463	250	150	100
450	513	250	150	100
500	563	275	175	100
600	663	275	175	100


Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr


Bogen 90° mit Tür

Art.-Nr. 3535-	D	Da	A	B	S
	113	176	230	160	70
	130	193	250	180	70
	150	213	270	200	70
	160	223	253	183	70
	180	243	305	205	100
	200	263	315	215	100
	250	313	340	240	100
	300	363	365	265	100
	350	413	390	290	100
	400	463	415	315	100
	450	513	440	340	100
	500	563	465	365	100
	600	663	515	415	100




Längenausgleichselement (Dämmwolle lose) kl.

Art.-Nr. 3526- kl	D	Da	A	B	S
	113	176	340-440	270-370	70
	130	193	340-440	270-370	70
	150	213	340-440	270-370	70
	160	223	340-440	270-370	70
	180	243	370-440	270-340	100
	200	263	370-440	270-340	100
	250	313	370-440	270-340	100
	300	363	370-440	270-340	100
	350	413	370-440	270-340	100
	400	463	370-440	270-340	100
	450	513	370-440	270-340	100
	500	563	370-440	270-340	100
	600	663	370-440	270-340	100




Bogen 90° ohne Tür

Art.-Nr. 3535- ot	D	Da	A	B	S
	113	176	230	160	70
	130	193	250	180	70
	150	213	270	200	70
	160	223	253	183	70
	180	243	305	205	100
	200	263	315	215	100
	250	313	340	240	100
	300	363	365	265	100
	350	413	390	290	100
	400	463	415	315	100
	450	513	440	340	100
	500	563	465	365	100
	600	663	515	415	100




Längenelement mit Messstutzen

Art.-Nr. 3541-	D	Da	A	B	S
	113	176	250	180	70
	130	193	250	180	70
	150	213	250	180	70
	160	223	250	180	70
	180	243	333	233	100
	200	263	333	233	100
	250	313	333	233	100
	300	363	333	233	100
	350	413	333	233	100
	400	463	333	233	100
	450	513	333	233	100
	500	563	333	233	100
	600	663	333	233	100




Prüföffnung

Art.-Nr. 3552-	D	Da	A	B	S
	113	176	400	330	70
	130	193	400	330	70
	150	213	400	330	70
	160	223	400	330	70
	180	243	450	350	100
	200	263	450	350	100
	250	313	450	350	100
	300	363	450	350	100
	350	413	450	350	100
	400	463	450	350	100
	450	513	450	350	100
	500	563	450	350	100
	600	663	450	350	100




Längenelement mit Kondensatablauf

Art.-Nr. 3542-	D	Da	A	B	S
	113	176	250	180	70
	130	193	250	180	70
	150	213	250	180	70
	160	223	250	180	70
	180	243	333	233	100
	200	263	333	233	100
	250	313	333	233	100
	300	363	333	233	100
	350	413	333	233	100
	400	463	333	233	100
	450	513	333	233	100
	500	563	333	233	100
	600	663	333	233	100




Längenausgleichselement (Dämmwolle lose) gr.

Art.-Nr. 3526- gr	D	Da	A	B	S
	113	176	420-600	350-530	70
	130	193	420-600	350-530	70
	150	213	420-600	350-530	70
	160	223	420-600	350-530	70
	180	243	450-570	350-470	100
	200	263	450-570	350-470	100
	250	313	450-570	350-470	100
	300	363	450-570	350-470	100
	350	413	450-570	350-470	100
	400	463	450-570	350-470	100
	450	513	450-570	350-470	100
	500	563	450-570	350-470	100
	600	663	450-570	350-470	100



Dampfsperrendurchführung, auch mit Winkelangabe

Art.-Nr. 3591-	D	Da	A	C
	113	206	280 - 530	400
	130	223	280 - 530	450
	150	243	280 - 530	450
	160	253	280 - 530	450
	180	273	280 - 530	500
	200	293	280 - 530	500
	250	343	280 - 530	550
	300	393	280 - 530	600
	350	443	280 - 530	650
	400	493	280 - 530	700
	450	543	280 - 530	750
	500	593	280 - 530	800
	600	693	280 - 530	900



Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr

Verschlusskappe


Art.-Nr. 3501-



D	Da	A	S
113	176	90	70
130	193	90	70
150	213	90	70
160	223	90	70
180	243	125	100
200	263	125	100
250	313	125	100
300	363	125	100
350	413	125	100
400	463	125	100
450	513	125	100
500	563	125	100
600	663	125	100

Übergangsstück Dw / Ew feuchunempfindlich


Art.-Nr. 3568-



D	Da	A	S
113	176	200	70
130	193	200	70
150	213	200	70
160	223	200	70
180	243	250	100
200	263	250	100
250	313	250	100
300	363	250	100
350	413	250	100
400	463	250	100
450	513	250	100
500	563	250	100
600	663	250	100

Ew Anschlussverlängerung mit dopp. Muffe


Art.-Nr. 4750-



D	Da	A	B	S
113	176	575	510	65
130	193	575	510	65
150	213	575	510	65
160	223	575	510	65
180	243	575	510	65
200	263	575	510	65
250	313	575	510	65
300	363	575	510	65
350	413	575	510	65
400	463	575	510	65
450	513	575	510	65
500	563	575	510	65
600	663	575	510	65

Reinigung Festbrennstoff, mit Kasten eckig


Art.-Nr. 3539-



D	Da	A	B	C	S
113	176	450	380	139	70
130	193	450	380	147	70
150	213	450	380	157	70
160	223	450	380	162	70
180	243	500	400	172	100
200	263	500	400	182	100
250	313	500	400	207	100
300	363	500	400	232	100
350	413	500	400	257	100
400	463	500	400	282	100
450	513	500	400	307	100
500	563	500	400	332	100
600	663	500	400	382	100

Übergangsstück Dw / Ew festbrennstoffe

Art.-Nr. 3538-




D	Da	DK
113	176	
130	193	
150	213	
160	223	
180	243	
200	263	
250	313	
300	363	
350	413	
400	463	
450	513	
500	563	
600	663	

DK ist gleich D
z.b.
D150 / DK150

Reinigung, feuchunempfindlich, mit Kasten eckig


Art.-Nr. 3551-



D	Da	A	B	C	S
113	176	450	380	139	70
130	193	450	380	147	70
150	213	450	380	157	70
160	223	450	380	162	70
180	243	500	400	172	100
200	263	500	400	182	100
250	313	500	400	207	100
300	363	500	400	232	100
350	413	500	400	257	100
400	463	500	400	282	100
450	513	500	400	307	100
500	563	500	400	332	100
600	663	500	400	382	100

Übergangsstück Dw / Ew reduziert

Art.-Nr. 3543-




D	Da	DK
113	176	
130	193	
150	213	
160	223	
180	243	
200	263	
250	313	
300	363	
350	413	
400	463	
450	513	
500	563	
600	663	

Größe angeben
z.b.
D150 / Dk130

Reinigung mit Tür rund Ø150, für Aussen

Art.-Nr. 3539- R




D	Da	A	B	C	H	S
113	176	400	330	143	140	70
130	193	400	330	152	140	70
150	213	400	330	162	140	70
160	223	400	330	167	140	70
180	243	500	400	177	160	100
200	263	500	400	187	160	100
250	313	500	400	212	160	100
300	363	500	400	237	160	100
350	413	500	400	262	160	100
400	463	500	400	287	160	100
450	513	500	400	312	160	100
500	563	500	400	337	160	100
600	663	500	400	387	160	100

Doppelwandige Schornsteinabgassysteme

Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr


Wandhalter 50 mm fest

Art.-Nr. 3524-	D	Da	A	B	C
	113	176	40		176
	130	193	40		193
	150	213	40		213
	160	223	40	Rohr	223
	180	243	40	hat	243
	200	263	40	einen Wandab-	563
	250	313	40	stand	313
	300	363	80	von	363
	350	413	80	50 mm	413
	400	463	80		463
	450	513	80		513
	500	563	80		563
	600	663	80		663




Wandkonsole 50 mm fest

Art.-Nr. 3546-	D	Da	A	B	C
	113	176	400		290
	130	193	400		290
	150	213	400		290
	160	223	400	Rohr	320
	180	243	400	hat	320
	200	263	600	einen Wandab-	360
	250	313	600	stand	410
	300	363	700	von	460
	350	413	700	50 mm	510
	400	463	700		560
	450	513	700		610
	500	563	700		660
	600	663	700		760




Wandhalter verstellbar

Art.-Nr. 3559-	D	Da	A	B	C
	113	176	40		176
	130	193	40		193
	150	213	40	65-110	213
	160	223	40	95-155	223
	180	243	40	140-200	243
	200	263	40	185-245	263
	250	313	40	230-290	313
	300	363	60	275-335	363
	350	413	60	andere	413
	400	463	60	Größen auf	463
	450	513	60	Anfänge	513
	500	563	60		563
	600	663	60		663




Wandkonsole verstellbar

Art.-Nr. 3556-	D	Da	A, B	C
	113	176	B Maß	290
	130	193	65-110	290
	150	213	95-155	290
	160	223	140-200	320
	180	243	185-245	320
	200	263	230-290	360
	250	313	275-335	410
	300	363		460
	350	413	A Maß	510
	400	463	wird	560
	450	513	von uns	610
	500	563	festgelegt	660
	600	663		760




Fundamentverankerung mit Ablauf für Wandkonsole

Art.-Nr. 3544-	D	Da	A	C
	113	176	90	290
	130	193	90	290
	150	213	90	290
	160	223	90	320
	180	243	125	320
	200	263	125	360
	250	313	125	410
	300	363	125	460
	350	413	125	510
	400	463	125	560
	450	513	125	610
	500	563	125	660
	600	663	125	760




Anschluss und Reinigung eckig, gegenüberliegend

Art.-Nr. 3554-	D	Da	A	B	C	H	S
	113	176	450	380	105	155	70
	130	193	450	380	115	155	70
	150	213	450	380	125	155	70
	160	223	450	380	140	155	70
	180	243	510	410	145	160	100
	200	263	510	410	155	160	100
	250	313	560	460	180	180	100
	300	363	610	510	205	205	100
	350	413	660	560	230	230	100
	400	463	710	610	255	255	100
	450	513	780	680	290	290	100
	500	563	810	710	305	305	100
	600	663	910	810	355	355	100




Rußtopf mit u. ohne Ablauf, mit Klemmband

Art.-Nr. 3525-	D	Da	A	S
	113	176	90	70
	130	193	90	70
	150	213	90	70
	160	223	90	70
	180	243	125	100
	200	263	125	100
	250	313	125	100
	300	363	125	100
	350	413	125	100
	400	463	125	100
	450	513	125	100
	500	563	125	100
	600	663	125	100



Anschluss und Reinigung rund, gegenüberliegend

Art.-Nr. 3554- R	D	Da	A	B	C	H	S
	113	176					
	130	193					
	150	213	423	353	125	170	70
	160	223	400	330	140	160	70
	180	243	490	390	145	145	100
	200	263	510	410	155	155	100
	250	313	560	460	180	180	100
	300	363	610	510	205	205	100
	350	413	660	560	230	230	100
	400	463	710	610	255	255	100
	450	513	780	680	290	290	100
	500	563	810	710	305	305	100
	600	663	910	810	355	355	100




Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr

Bodenhocker neue Ausführung


Art.-Nr. 3555-



D	Da	A	C
113	176	121	195
130	193	121	215
150	213	121	235
160	223	121	245
180	243	151	265
200	263	151	285
250	313	151	335
300	363	151	385
350	413	151	435
400	463	151	485
450	513	151	535
500	563	151	585
600	663	151	685

Sprung mit 2xWinkel 15°


Art.-Nr.



D	Da	A	B	C	S
113	176	424	354	47	70
130	193	424	354	47	70
150	213	424	354	47	70
160	223	424	354	47	70
180	243	560	460	61	100
200	263	560	460	61	100
250	313	560	460	61	100
300	363	560	460	61	100
350	413	690	590	78	100
400	463	690	590	78	100
450	513	690	590	78	100
500	563	690	590	78	100
600	663	690	590	78	100

Bodenhocker neue Ausführung kürzbar


Art.-Nr. 3555- V



D	Da	A	C
113	176	250 - 508	195
130	193	250 - 508	215
150	213	250 - 508	235
160	223	250 - 508	245
180	243	250 - 478	265
200	263	250 - 478	285
250	313	250 - 478	335
300	363	250 - 478	385
350	413	250 - 478	435
400	463	250 - 478	485
450	513	250 - 478	535
500	563	250 - 478	585
600	663	250 - 478	685

Sprung mit 2xWinkel 30°

Art.-Nr.



D	Da	A	B	C	S
113	176	406	336	90	70
130	193	406	336	90	70
150	213	406	336	90	70
160	223	406	336	90	70
180	243	537	437	117	100
200	263	537	437	117	100
250	313	537	437	117	100
300	363	660	560	150	100
350	413	660	560	150	100
400	463	660	560	150	100
450	513	660	560	150	100
500	563	753	653	175	100
600	663	753	653	175	100

Teleskopstange, verschiedene Verstellbereiche


Art.-Nr. Tel-



D	Da	A (Verstellbereiche)
113	176	
130	193	
150	213	
160	223	1000 - 1500
180	243	1500 - 2000
200	263	2000 - 2500
250	313	2500 - 3000
300	363	3000 - 3500
350	413	3500 - 4000
400	463	4000 - 4500
450	513	
500	563	
600	663	

Sprung mit 2xWinkel 45°


Art.-Nr.



D	Da	A	B	C	S
113	176	428	358	148	70
130	193	428	358	148	70
150	213	428	358	148	70
160	223	428	358	148	70
180	243	612	512	212	100
200	263	612	512	212	100
250	313	612	512	212	100
300	363	783	683	283	100
350	413	783	683	283	100
400	463	783	683	283	100
450	513	783	683	283	100
500	563	868	768	318	100
600	663	868	768	318	100

Bw-Hocker kürzbar, mit Bogen 90°


Art.-Nr. 3745-



D	Da	A	Br
113	176	676-418	446-188
130	193	705-447	455-197
150	213	735-477	465-207
160	223	723-465	470-212
180	243	785-557	480-252
200	263	805-577	490-262
250	313	855-627	515-287
300	363	905-677	540-312
350	413	955-727	565-337
400	463	1005-777	590-362
450	513	1055-827	615-387
500	563	1105-877	640-412
600	663	1205-977	690-462

Wand u. Deckendurchführung, auch mit Winkelang.

Art.-Nr. 3519-




D	Da	A	C
113	206	280 - 530	400
130	223	280 - 530	450
150	243	280 - 530	450
160	253	280 - 530	450
180	273	280 - 530	500
200	293	280 - 530	500
250	343	280 - 530	550
300	393	280 - 530	600
350	443	280 - 530	650
400	493	280 - 530	700
450	543	280 - 530	750
500	593	280 - 530	800
600	693	280 - 530	900

Doppelwandige Schornsteinabgassysteme



Werkstoff-Nr. 1.4404 Innenrohr
1.4301 Außenrohr


Sprung mit 2xWinkel 15°, mit Rohr 250 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	598	528	93	70
	130	193	598	528	93	70
	150	213	598	528	93	70
	160	223	598	528	93	70
	180	243	705	605	99	100
	200	263	705	605	99	100
	250	313	705	605	99	100
	300	363	705	605	99	100
	350	413	835	735	116	100
	400	463	835	735	116	100
	450	513	835	735	116	100
	500	563	835	735	116	100
	600	663	835	735	116	100


Sprung mit 2xWinkel 30°, mit Rohr 250 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	562	492	180	70
	130	193	562	492	180	70
	150	213	562	492	180	70
	160	223	562	492	180	70
	180	243	667	567	192	100
	200	263	667	567	192	100
	250	313	667	567	192	100
	300	363	790	690	225	100
	350	413	790	690	225	100
	400	463	790	690	225	100
	450	513	790	690	225	100
	500	563	883	783	250	100
	600	663	883	783	250	100


Sprung mit 2xWinkel 15°, mit Rohr 333 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	678	608	115	70
	130	193	678	608	115	70
	150	213	678	608	115	70
	160	223	678	608	115	70
	180	243	785	685	121	100
	200	263	785	685	121	100
	250	313	785	685	121	100
	300	363	785	685	121	100
	350	413	915	815	138	100
	400	463	915	815	138	100
	450	513	915	815	138	100
	500	563	915	815	138	100
	600	663	915	815	138	100


Sprung mit 2xWinkel 30°, mit Rohr 333 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	634	564	222	70
	130	193	634	564	222	70
	150	213	634	564	222	70
	160	223	634	564	222	70
	180	243	739	639	234	100
	200	263	739	639	234	100
	250	313	739	639	234	100
	300	363	862	762	267	100
	350	413	862	762	267	100
	400	463	862	762	267	100
	450	513	862	762	267	100
	500	563	955	855	292	100
	600	663	955	855	292	100


Sprung mit 2xWinkel 15°, mit Rohr 500 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	839	769	246	70
	130	193	839	769	246	70
	150	213	839	769	246	70
	160	223	839	769	246	70
	180	243	946	846	164	100
	200	263	946	846	164	100
	250	313	946	846	164	100
	300	363	946	846	164	100
	350	413	1076	976	181	100
	400	463	1076	976	181	100
	450	513	1076	976	181	100
	500	563	1076	976	181	100
	600	663	1076	976	181	100


Sprung mit 2xWinkel 30°, mit Rohr 500 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	778	708	305	70
	130	193	778	708	305	70
	150	213	778	708	305	70
	160	223	778	708	305	70
	180	243	883	783	317	100
	200	263	883	783	317	100
	250	313	883	783	317	100
	300	363	1006	906	350	100
	350	413	1006	906	350	100
	400	463	1006	906	350	100
	450	513	1006	906	350	100
	500	563	1100	1000	375	100
	600	663	1100	1000	375	100

Sprung mit 2xWinkel 15°, mit Rohr 1000 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	1322	1252	287	70
	130	193	1322	1252	287	70
	150	213	1322	1252	287	70
	160	223	1322	1252	287	70
	180	243	1429	1329	294	100
	200	263	1429	1329	294	100
	250	313	1429	1329	294	100
	300	363	1429	1329	294	100
	350	413	1559	1459	311	100
	400	463	1559	1459	311	100
	450	513	1559	1459	311	100
	500	563	1559	1459	311	100
	600	663	1559	1459	311	100

Sprung mit 2xWinkel 30°, mit Rohr 1000 mm

Art.-Nr.	D	Da	A	B	C	S
	113	176	1211	1141	555	70
	130	193	1211	1141	555	70
	150	213	1211	1141	555	70
	160	223	1211	1141	555	70
	180	243	1316	1216	567	100
	200	263	1316	1216	567	100
	250	313	1316	1216	567	100
	300	363	1439	1339	600	100
	350	413	1439	1339	600	100
	400	463	1439	1339	600	100
	450	513	1439	1339	600	100
	500	563	1533	1433	625	100
	600	663	1533	1433	625	100