


Werkstoff-Nr. 4404

Rohr 1000 mm


Art.-Nr. 4705-Ø



D	A	B	S
113	1000	930	70
120	1000	930	70
130	1000	930	70
140	1000	930	70
150	1000	930	70
160	1000	930	70
180	1000	900	100
200	1000	900	100
250	1000	900	100
300	1000	900	100
350	1000	900	100
400	1000	900	100
500	1000	900	100
600	1000	900	100

Rohr mit Kondensatablauf


Art.-Nr. 4716-Ø



D	A	B	S
110	250	180	70
120	250	180	70
130	250	180	70
140	250	180	70
150	250	180	70
160	250	180	70
180	333	233	100
200	333	233	100
250	333	233	100
300	333	233	100
350	333	233	100
400	333	233	100
500	333	233	100
600	333	233	100

Rohr 500 mm


Art.-Nr. 4709-Ø



D	A	B	S
113	500	430	70
120	500	430	70
130	500	430	70
140	500	430	70
150	500	430	70
160	500	430	70
180	500	400	100
200	500	400	100
250	500	400	100
300	500	400	100
350	500	400	100
400	500	400	100
500	500	400	100
600	500	400	100

Kesselanschluss


Art.-Nr. 4711-Ø



D	Dk (Kessel)	A
113	110	150
120	120	150
130	130	150
140	140	150
150	150	150
160	160	150
180	180	150
200	200	150
250	250	150
300	300	150
350	350	150
400	400	150
500	500	150
600	600	150

Rohr 250 mm


Art.-Nr. 4715-Ø



D	A	B	C
113	250	180	70
120	250	180	70
130	250	180	70
140	250	180	70
150	250	180	70
160	250	180	70
180	250	150	100
200	250	150	100
250	250	150	100
300	250	150	100
350	250	150	100
400	250	150	100
500	250	150	100
600	250	150	100

Prüföffnung


Art.-Nr. 4714-Ø



D	A	B	S
110	333	263	70
120	333	263	70
130	333	263	70
140	333	263	70
150	333	263	70
160	333	263	70
180	350	250	100
200	350	250	100
250	350	250	100
300	350	250	100
350	350	250	100
400	350	250	100
500	350	250	100
600	350	250	100

Rohr mit Meßöffnung


Art.-Nr. 4717-Ø



D	A	B	S
110	250	180	70
120	250	180	70
130	250	180	70
140	250	180	70
150	250	180	70
160	250	180	70
180	333	233	100
200	333	233	100
250	333	233	100
300	333	233	100
350	333	233	100
400	333	233	100
500	333	233	100
600	333	233	100

Justierrohr 300 mm incl. Dichtsatz

Art.-Nr. 4718-Ø




D	A	B	S
110	420-600	350-530	70
120	420-600	350-530	70
130	420-600	350-530	70
140	420-600	350-530	70
150	420-600	350-530	70
160	420-600	350-530	70
180	450-570	350-470	100
200	450-570	350-470	100
250	450-570	350-470	100
300	450-570	350-470	100
350	450-570	350-470	100
400	450-570	350-470	100
500	450-570	350-470	100
600	450-570	350-470	100

Werkstoff-Nr. 4404

Bogen 90° starr, m.t, 3-Seg. Kondensatdicht gep.


Art.-Nr. 4769-Ø



D	A	B	S
110	222	152	70
120	223	153	70
130	224	154	70
140	224	154	70
150	225	155	70
160	226	156	70
180	278	178	100
200	280	180	100
250	309	209	100
300	338	238	100
350	367	267	100
400	372	272	100
500	430	330	100
600	489	389	100

Bogen drehb. 0°- 90° m.t, 3-Segmente


Art.-Nr. 4069-Ø



D	A	B	S
110	222	152	70
120	223	153	70
130	224	154	70
140	224	154	70
150	225	155	70
160	226	156	70
180	278	178	100
200	280	180	100
250	309	209	100
300	338	238	100
350	367	267	100
400	372	272	100
500	430	330	100
600	489	389	100

Bogen drehb. 0°- 90° m.t, 3-Seg. m. Dichtung


Art.-Nr. 4768-Ø



D	A	B	S
110	222	152	70
120	223	153	70
130	224	154	70
140	224	154	70
150	225	155	70
160	226	156	70
180	278	178	100
200	280	180	100
250	309	209	100
300	338	238	100
350	367	267	100
400	372	272	100
500	430	330	100
600	489	389	100

Bogen drehb. 0°- 90° m.t 4-Segmente


Art.-Nr. 4775-Ø



D	A	B	S
110	218	248	70
120	217	147	70
130	219	149	70
140			
150	215	145	70
160			
180			
200			
250			
300			
350			
400			
500			
600			

Winkel 45°


Art.-Nr. 4771-Ø



D	A	B	S
110	125	55	70
120	125	55	70
130	125	55	70
140	125	55	70
150	125	55	70
160	125	55	70
180	167	67	100
200	167	67	100
250	200	100	100
300	200	100	100
350	250	150	100
400	250	150	100
500	250	150	100
600	275	175	100

2 x Winkel 45°


Art.-Nr.



D	A	B	C	S
110	377	307	127	70
120	377	307	127	70
130	377	307	127	70
140	377	307	127	70
150	377	307	127	70
160	377	307	127	70
180	499	399	165	100
200	499	399	165	100
250	612	512	212	100
300	612	512	212	100
350	783	683	283	100
400	783	683	283	100
500	783	683	283	100
600	868	768	318	100

Winkel 45° mit Tür

Art.-Nr. 4773-Ø T



D	A	B	C	S
110	210	140	123	70
120	208	138	125	70
130	208	138	125	70
140	208	138	125	70
150	208	138	125	70
160	237	167	138	70
180	227	127	173	100
200	200	100	200	100
250	239	139	171	100
300	250	150	250	100
350	250	150	250	100
400	250	150	250	100
500	250	150	250	100
600	275	175	275	100

Klemmband

Art.-Nr. 4958-Ø




D	A
110	30
120	30
130	30
140	30
150	30
160	30
180	30
200	30
250	30
300	30
350	30
400	30
500	30
600	30

Werkstoff-Nr. 4404

Wandfutter einfach

Art.-Nr. 4752-Ø




D	A
110	80
120	80
130	80
140	80
150	80
160	80
180	80
200	80
250	80
300	80
350	80
400	80
500	80
600	80

Sonderlängen
auf
Anfrage
möglich

Verschlusskappe

Art.-Nr. 4908-Ø




D
110
120
130
140
150
160
180
200
250
300
350
400
500
600

Angabe des
Verwendungszwecks.
z.B.:

Verschluss eines
Wandfutters,
Anschlusses
oder
sonstiges

Wandfutter doppelt

Art.-Nr. 4751-Ø



D	A
110	80
120	80
130	80
140	80
150	80
160	80
180	80
200	80
250	80
300	80
350	80
400	80
500	80
600	80

Sonderlängen
auf
Anfrage
möglich

Tür für Bogen


Art.-Nr. 4917-Ø



D
110
120
130
140
150
160
180
200
250
300
350
400
500
600

Silikondichtung

Art.-Nr. 4601-Ø



D	A
110	30
120	30
130	30
140	30
150	30
160	30
180	30
200	30
250	30
300	30
350	30
400	30
500	30
600	30

Reduzier-/Erweiterungsstück m. dopp. Wandfutter

Art.-Nr. 4907Ø



D
113
120
130
140
150
160
180
200
250
300
350
400
500
600

Teleskopstütze

Art.-Nr. 4688-Ø




D
110
120
130
140
150
160
180
200
250
300
350
400
500
600

Verstellbereich
300-500 mm

Dichtmanschette (Stck.)

Art.-Nr. 4777-Ø




D	A
110	100
120	100
130	100
140	100
150	100
160	100
180	100
200	100
250	100
300	100
350	100
400	100
500	100
600	100

Sonderlängen
auf
Anfrage
möglich

Werkstoff-Nr. 4404

Abgasschalldämpfer bis 20 dB (A)


Art.-Nr. 20-Ø



D	Da	A	B	C	S
113					
120					
130	252	504	434	337	70
140					
150	252	504	434	337	70
160	252	504	434	337	70
180	302	637	537	470	100
200	302	637	537	470	100
250	450	962	862	712	100
300	500	1122	1022	862	100
350	550	1272	1172	1012	100
400					
500					
600					

Abgasschalldämpfer bis 20 dB (A) druckdicht

Art.-Nr. 20-Ø D



D	Da	A	B	C	S
113					
120					
130	252	504	434	337	70
140					
150	252	504	434	337	70
160	252	504	434	337	70
180	302	637	537	470	100
200	302	637	537	470	100
250	450	962	862	712	100
300	500	1122	1022	862	100
350	550	1272	1172	1012	100
400					
500					
600					